

```

----- TELNET - MANAGER MODE -----
Switch Configuration - VLAN - VLAN Port Assignment

Port      Vlan1-FW      vlan2-wifi      vlan-srv      vlan-wifi2
-----+-----
1         No            No              Untagged      No
2         Untagged     No              No             No
3         Untagged     No              No             No
4         Untagged     No              No             No
5         Untagged     No              No             No
6         Untagged     No              No             No
7         Untagged     No              No             No
8         Untagged     No              No             No
9         Untagged     No              No             No
10        Untagged     No              No             No
11        Untagged     No              No             No
12        Untagged     No              No             No
-----+-----
13        Untagged     No              No             No
14        Untagged     No              No             No
15        Untagged     No              No             No
16        No            Untagged       No             Tagged
17        Untagged     No              No             No
18        Untagged     No              No             No
19        Untagged     No              No             No
20        Untagged     No              No             No
21        Untagged     No              No             No
22        Untagged     No              No             No
23        Untagged     No              No             No
24        Untagged     No              No             No
-----+-----
25        Untagged     Tagged          Tagged         Tagged
26        Untagged     No              No             No
27        Untagged     No              No             No
28        Untagged     No              No             No

Actions->  Cancel    Edit    Save    Help

```

```

ProCurve Switch 2610-24                      15-Jan-1990   2:34:15
----- TELNET - MANAGER MODE -----
Switch Configuration - Internet (IP) Service

IP Routing : Disabled

Default Gateway : 192.168.5.1
Default TTL     : 64
Arp Age         : 20

-----+-----
VLAN          IP Config      IP Address      Subnet Mask
-----+-----
Vlan1-FW      | Manual        192.168.5.2    255.255.255.0
vlan2-wifi    | Disabled
vlan-srv      | Disabled
vlan-wifi2    | Disabled

```

25 g0/0 < FW (transport vlans _ tagged)

1 fa1 > cq56 www server (vlan-srv sur l'interface _ untagged)

16 fa16 > wifi borne (vlan2-wifi sur l'interface _ untagged)

(vlan-wifi2 transport sur l'interface _ tagged)